


Data sheet


valid from: 4/9/26














3-Way ball valve type 543 Pro PVC-C
Horizontal/T-port
With solvent cement sockets metric

Model:

- Lockable lever as standard (DN10-DN50)
- For easy installation and removal (valve end and union nut are compatible with type 546)
- Ball seals PTFE
- Angle of operation 360° without turn limiter
- Turn limiter 90° enclosed, in different positions usable as a clip-on ring
- Integrated stainless steel mounting inserts
- Delivery status A-B-C opened, see flow scheme
- Z-dimension, valve end and union nut are compatible with type 543 (1stGeneration)

Option:

- Interface-module with position feedback sensor, incl. LED feedback (DN10-50)
- Manual spring return lever ("Dead man") (DN10-25)
- Pneumatic or electric actuators from GF
- Individual configuration of the valve possible

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value (Δp=1 bar) (l/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
16	10	⅜	10	140	**163 543 201**	1	0.264	**163 543 211**	1	0.264
20	15	½	10	200	**163 543 202**	1	0.271	**163 543 212**	1	0.271
25	20	¾	10	470	**163 543 203**	1	0.389	**163 543 213**	1	0.389
32	25	1	10	793	**163 543 204**	1	0.561	**163 543 214**	1	0.590
40	32	1 ¼	10	1290	**163 543 205**	1	1.007	**163 543 215**	1	1.007
50	40	1 ½	10	1910	**163 543 206**	1	1.487	**163 543 216**	1	1.487
63	50	2	10	3100	**163 543 207**	1	2.889	**163 543 217**	1	2.889

d (mm)	D (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	L6 (mm)	M	z (mm)	z1 (mm)	closest inch (inch)
16	50	61	28	8	109	82	73	36	25	35	47	6	81	40	⅜
20	50	61	28	8	112	82	73	36	25	35	47	6	81	40	½
25	58	74	32	8	131	106	86	43	25	44	62	6	94	47	¾
32	68	80	36	8	151	106	99	50	25	44	62	6	107	54	1
40	84	95	45	9	181	131	120	60	45	57	74	8	130	65	1 ¼
50	97	102	51	9	205	131	137	69	45	57	74	8	143	72	1 ½
63	124	117	65	9	261	152	179	89	45	66	86	8	185	92	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com