

Data sheet

valid from: 8/26/26





PROGEF Standard
Diaphragm valve type 514
With fusion sockets metric

Model:

- Material: PP-H
- Double flow rate compared to predecessor
- One housing nut replaces four screws
- Handwheel with built-in locking mechanism
- For easy installation and removal
- Short overall length

Option:

- Individual configuration of the valve
- Self adjusting multifunctional module with integrated limit switches

* O-Ring material: FKM

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value (Δp=1 bar) (l/min)
20	15	½	10	125
25	20	¾	10	271
32	25	1	10	481
40	32	1 ¼	10	759
50	40	1 ½	10	1263
63	50	2	10	1728

d (mm)	NBR Code	EPDM Code	PTFE/EPDM Code	FKM Code	Weight (kg)
20	**167 514 002**	**167 514 012**	**167 514 032**	**167 514 062**	0.267
25	**167 514 003**	**167 514 013**	**167 514 033**	**167 514 063**	0.391
32	**167 514 004**	**167 514 014**	**167 514 034**	**167 514 064**	1.151
40	**167 514 005**	**167 514 015**	**167 514 035**	**167 514 065**	1.277
50	**167 514 006**	**167 514 016**	**167 514 036**	**167 514 066**	1.386
63	**167 514 007**	**167 514 017**	**167 514 037**	**167 514 067**	3.030

d (mm)	D (mm)	D2 (mm)	D3 (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L2 (mm)	M	z (mm)	Lift = Hx (mm)	closest inch (inch)
20	65	65	48	73	14	12	128	25	M6	96	7	½
25	80	65	58	81	18	12	150	25	M6	114	10	¾
32	88	87	65	107	22	12	162	25	M6	122	13	1
40	101	87	79	115	26	15	184	45	M8	140	15	1 ¼
50	117	135	91	148	32	15	210	45	M8	160	19	1 ½
63	144	135	111	166	39	15	248	45	M8	190	25	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com