Data sheet

valid from: 9/15/26




PROGEF Standard
Butterfly valve type 567
Hand lever with ratchet settings


Model:


- Material: PP-H, DN350-DN600 material PP-R
- Up to DN 300: Overall length according to EN558 (DN 50-200: line 25, DN250, 300 line 16), ISO 5752
- Connecting dimension: ISO 7005 PN 10, EN 1092 PN 10, DIN 2501 PN 10, ANSI/ASME B 16.5 Class 150, BS 1560: 1989, BS 4504, JIS B 2220
- We recommend for the dimensions DN250 and DN300 only 6 bar maximum system pressure for the hand lever version

Note:

For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com







d (mm)	Size (inch)	DN (mm)	PN (bar)	kv-value (Δp=1 bar) (l/min)	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
63	2	50	10	740	**167 567 002**	1.170	**167 567 022**	1.627
75	2 ½	65	10	1500	**167 567 003**	1.254	**167 567 023**	1.061
90	3	80	10	2400	**167 567 004**	1.384	**167 567 024**	1.404
110	4	100	10	3800	**167 567 005**	1.961	**167 567 025**	1.998
140	5	125	10	8600	**167 567 006**	2.367	**167 567 026**	2.429
160	6	150	10	11400	**167 567 007**	3.741	**167 567 027**	3.246
225	8	200	10	19900	**167 567 008**	5.545	**167 567 028**	5.609
280	10	250	6	34000	**167 567 009**	11.061	**167 567 029**	11.841
315	12	300	6	50000	**167 567 010**	16.548	**167 567 030**	13.245

d (mm)	PTFE Code	Weight (kg)
63	**167 567 202**	1.170
75	**167 567 203**	1.254
90	**167 567 204**	1.384
110	**167 567 205**	1.961
140	**167 567 206**	2.367
160	**167 567 207**	3.741
225	**167 567 208**	5.545
280	**167 567 209**	11.061
315	**167 567 210**	16.548

d (mm)	Hmax (mm)	Lmax (mm)	Wmax (mm)	U (mm)	V (mm)	H4 (mm)	V1 (mm)	Lg (mm)	D2 (mm)	Q1 (mm)	Q2 (mm)	Y (mm)	M1 (mm)	M2 (mm)
63	278.9	115.2	269.0	90	133.3	23	78.8	45	104	40		66.8	64.7	205.5
75	291.8	115.2	281.8	90	139.9	23	85.1	46	115	54	35	66.8	64.7	205.5
90	303.6	115.2	273.9	90	145.6	23	91.2	49	131	67	50	66.8	64.7	205.5
110	342.2	115.2	336.0	90	166.4	23	105.7	56	161	88	74	70.1	64.9	255.5
140	368.9	115.2	349.0	90	180.0	23	118.8	64	187	113	97	70.1	64.9	255.5
160	390.0	115.2	363.0	90	189.0	23	130.9	72	215	139	123	70.1	64.9	255.5
225	455.1	149.4	543.0	90	210.5	23	158.3	73	267	178	169	86.3	103.6	409.5
280	555.0	149.4	574.0	125	262.6	23	206.1	113	329	210	207	86.3	103.6	409.5
315	599.4	149.4	599.7	125	284.3	23	228.8	113	379	256	253	86.3	103.6	409.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com