
Data sheet

valid from: 3/27/26





Line strainer type 305 ABS
With solvent cement spigots metric

Model:

- Protects valves, pumps, etc. from becoming soiled
- Easy dismantling for cleaning the screens
- Overall length EN 558
- Cylindrical screen must be ordered separately
- Screen in stainless steel operable temperature range up -40°C to +60°C
- Screen in PVC-U operable temperature range up 0°C to +60°C

d (mm)	DN (mm)	PN (bar)	EPDM Code	SP	Weight (kg)	D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)	closest inch (inch)
20	15	10	**169 305 302**	1	0.081	48	65	124	130	28	½
25	20	10	**169 305 303**	1	0.120	54	76	144	150	37	¾
32	25	10	**169 305 304**	1	0.180	62	90	154	160	37	1
40	32	10	**169 305 305**	1	0.284	71	104	174	180	44	1 ¼
50	40	10	**169 305 306**	1	0.484	88	124	194	200	48	1 ½
63	50	10	**169 305 307**	1	0.780	103	148	224	230	60	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com