


Data sheet


valid from: 4/9/26














3-Way ball valve type 543 Pro ABS
Horizontal/T-port
With solvent cement sockets BS

Model:

- Lockable lever as standard (DN10-DN50)
- For easy installation and removal (valve end and union nut are compatible with type 546)
- Ball seals PTFE
- Angle of operation 360° without turn limiter
- Turn limiter 90° enclosed, in different positions usable as a clip-on ring
- Integrated stainless steel mounting inserts
- Delivery status A-B-C opened, see flow scheme
- Z-dimension, valve end and union nut are compatible with type 543 (1stGeneration)

Option:

- Interface-module with position feedback sensor, incl. LED feedback (DN10-50)
- Manual spring return lever ("Dead man") (DN10-25)
- Pneumatic or electric actuators from GF
- Individual configuration of the valve possible

d (mm)	Size (inch)	DN (mm)	PN (bar)	kv-value (Δp=1 bar) (l/min)	EPDM Code	SP	Weight (kg)
16	⅜	10	10	140	**169 543 261**	1	0.186
20	½	15	10	200	**169 543 262**	1	0.191
25	¾	20	10	470	**169 543 263**	1	0.274
32	1	25	10	793	**169 543 264**	1	0.415
40	1 ¼	32	10	1290	**169 543 265**	1	0.708
50	1 ½	40	10	1910	**169 543 266**	1	1.045
63	2	50	10	3100	**169 543 267**	1	2.030

D (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	L6 (mm)	M	z (mm)	z1 (mm)
50	61	28	8	109	82	73	36	25	35	47	6	77	38
50	61	28	8	112	82	73	36	25	35	47	6	77	38
58	74	32	8	131	106	86	43	25	44	62	6	90	45
68	80	36	8	151	106	99	50	25	44	62	6	103	52
84	95	45	9	181	131	120	60	45	57	74	8	124	62
97	102	51	9	205	131	137	69	45	57	74	8	145	73
124	117	65	9	261	152	179	89	45	66	86	8	189	94

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com