Data sheet

valid from: 4/7/26




Ball valve type 127 PVC-U
24V
With manual emergency override
With solvent cement sockets metric

Model:


- IP68 Rating
- Factory set control range 90°<)
- Heating element, position feedback (Open/Close)
- Integrated stainless steel mounting inserts

Option:


- Other valve and actuator configurations available
- Optional accessories: Fail-safe return unit



d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value (Δp=1 bar) (l/min)	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
16	10	⅜	10	70	**199 127 042**	2.122	**199 127 052**	2.072
20	15	½	10	185	**199 127 043**	2.122	**199 127 053**	2.125
25	20	¾	10	350	**199 127 044**	2.216	**199 127 054**	2.860
32	25	1	10	700	**199 127 045**	2.321	**199 127 055**	2.189
40	32	1 ¼	10	1000	**199 127 046**	3.831	**199 127 056**	2.592
50	40	1 ½	10	1600	**199 127 047**	2.809	**199 127 057**	3.437
63	50	2	10	3100	**199 127 048**	3.547	**199 127 058**	3.772



d (mm)	Actuator	B3 (mm)	DE1 (mm)	E (mm)	G (mm)	H (mm)	H1 (mm)	H4 (mm)	L (mm)	L1 (mm)	Lz (mm)	M (mm)	M1 (mm)	M2 (mm)	s1 (mm)
16	EA15	25	50	122	M6	197	27	12	114	33	28	161	77	83	3.0
20	EA15	25	50	122	M6	197	27	12	124	33	28	161	77	83	3.0
25	EA15	25	58	122	M6	201	30	12	144	33	33	161	77	83	3.0
32	EA15	25	68	122	M6	207	36	12	154	33	36	161	77	83	4.0
40	EA15	45	84	122	M8	213	44	15	174	33	43	161	77	83	4.5
50	EA15	45	97	122	M8	219	51	15	194	33	45	161	77	83	5.5
63	EA15	45	124	122	M8	234	64	15	224	33	51	161	77	83	7.0



d (mm)	z (mm)
16	88
20	96
25	112
32	118
40	134
50	148
63	170

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com