



Data sheet

valid from: 4/7/26









ABS Ball valve type 183
24V
With manual emergency override
With solvent cement sockets ABS BS

Model:

- IP68 Rating
- Factory set control range 90°<)
- Heating element, position feedback (Open/Close/ Middle)
- Integrated stainless steel mounting inserts

Option:

- Other valve and actuator configurations available
- Optional accessories: Monitoring board, Positioner, Profibus DP board, Modbus TCP EA 25-250 Ethernet Interface Card

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value (Δp=1 bar) (l/min)	EPDM Code	Weight (kg)
16	10	⅜	10	70	**199 183 822**	2.100
20	15	½	10	185	**199 183 823**	2.100
25	20	¾	10	350	**199 183 824**	2.200
32	25	1	10	700	**199 183 825**	2.300
40	32	1 ¼	10	1000	**199 183 826**	2.600
50	40	1 ½	10	1600	**199 183 827**	3.000
63	50	2	10	3100	**199 183 828**	3.535
75	65	2 ½	10	5000	**199 183 829**	6.300
90	80	3	10	7000	**199 183 830**	7.380
110	100	4	10	11000	**199 183 831**	11.500

d (mm)	Actuator	B3 (mm)	DE1 (mm)	G (mm)	E (mm)	H (mm)	H1 (mm)	H4 (mm)	L (mm)	L1 (mm)	Lz (mm)	M (mm)	M1 (mm)	M2 (mm)	z (mm)
16	EA25	25	50	M6	122	227	27	12	92	33	28	180	97	83	64
20	EA25	25	50	M6	122	227	27	12	95	33	28	180	97	83	64
25	EA25	25	58	M6	122	231	30	12	110	33	33	180	97	83	72
32	EA25	25	68	M6	122	237	36	12	123	33	36	180	97	83	79
40	EA25	45	84	M8	122	243	44	15	146	33	43	180	97	83	94
50	EA25	45	97	M8	122	249	51	15	157	33	45	180	97	83	95
63	EA25	45	124	M8	122	264	64	15	183	33	51	180	97	83	107
75	EA45	70	166	M8	122	313	85	15	233	33	68	180	98	82	144
90	EA45	70	200	M8	122	325	105	15	254	33	71	180	98	82	151
110	EA120	120	238	M12	122	363	123	22	301	33	82	180	98	82	174

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com