
Data sheet

valid from: 3/31/26





Elbow 90° PVC-U Rp

Model:

- With parallel female thread Rp
- Connection to plastic thread only
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	D (mm)	L (mm)
Rp	⅜	10	**721 101 605**	10	0.013	9	23	23
Rp	½	10	**721 101 606**	10	0.017	12	27	27
Rp	¾	10	**721 101 607**	10	0.029	15	33	33
Rp	1	10	**721 101 608**	10	0.042	19	39	39
Rp	1 ¼	10	**721 101 609**	10	0.070	27	48	49
Rp	1 ½	10	**721 101 610**	5	0.178	35	61	59
Rp	2	10	**721 101 611**	5	0.322	44	75	72

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com