
Data sheet

valid from: 3/31/26





Tee 90° PVC-U metric Rp

Model:

- With solvent cement socket metric, branch with parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

d (mm)	Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z1 (mm)	z2 (mm)	D (mm)	D1 (mm)	L (mm)
12	Rp	¼	16	**721 200 204**	10	0.015	7	7	17	20	19
16	Rp	⅜	16	**721 200 205**	10	0.027	9	9	21	25	23
20	Rp	½	16	**721 200 206**	10	0.029	11	13	26	30	29
25	Rp	¾	16	**721 200 207**	10	0.043	14	15	32	35	33
32	Rp	1	16	**721 200 208**	10	0.080	17	19	40	45	39
40	Rp	1 ¼	16	**721 200 209**	10	0.134	23	26	47	55	49
50	Rp	1 ½	16	**721 200 210**	5	0.212	27	36	59	59	59
63	Rp	2	16	**721 200 211**	5	0.379	33	46	74	75	71

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com