
Data sheet

valid from: 3/31/26





Tee 90° PVC-U BS Inch Rp

Model:

- With solvent cement socket BS Inch and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

Thread Type	Size (inch)	PN (bar)	d (inch)	Code	SP	Weight (kg)	z1 (mm)	z2 (mm)	D (mm)	D1 (mm)	L (mm)
Rp	⅜	16	⅜	**721 201 205**	10	0.028	10	14	25	25	26
Rp	½	16	½	**721 201 206**	10	0.028	10	13	30	26	29
Rp	¾	16	¾	**721 201 207**	10	0.039	13	15	35	32	33
Rp	1	16	1	**721 201 208**	10	0.111	17	19	45	40	39

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com