
Data sheet

valid from: 4/1/26





Full face flange PVC-U Inch BS
Drilled to universal standard

Model:

- In accordance with BS 10, DIN EN 1092 and ASME B 16.5
- Jointing face serrated
- Solvent cement socket BS inch
- It is recommended to use backing flanges in conjunction with all Full Face Flanges
- All Full Face Flanges are manufactured with outside diameter to BS EN 1092

AL: number of holes

d (inch)	DN (mm)	PN (bar)	Code	SP	Weight (kg)	H (mm)	AL	D2 (mm)	D3 (mm)	H1 (mm)	D1 (mm)	z (mm)	D (mm)
½	15	15	**721 733 106**	100	0.083	10	4	27	15	21	67	3	95
¾	20	9	**721 733 107**	50	0.106	10	4	33	15	24	73	3	105
1	25	9	**721 733 108**	50	0.129	10	4	41	15	27	83	3	115
1 ¼	32	9	**721 733 109**	30	0.189	10	4	50	15	32	87	3	140
1 ½	40	9	**721 733 110**	30	0.236	10	4	61	15	33	98	3	150
2	50	15	**721 733 111**	18	0.309	10	4	77	18	40	114	3	165
3	80	9	**721 733 113**	8	0.540	12	8	108	18	56	146	5	200
4	100	9	**721 733 114**	4	0.889	17	8	136	18	69	178	5	220
6	150	9	**721 733 117**	2	2.022	22	8	198	22	96	235	5	285

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com