

Data sheet

valid from: 4/4/26





Barrel nipple ABS metric

Model:

- For the shortest possible distance between fittings
- Overall length L = 2 x socket length
- With solvent cement spigots on both sides

d (mm)	Size (inch)	PN (bar)	Code	Weight (kg)	L (mm)	closest inch (inch)
20		16	**729 900 906**	0.008	32	½
25		16	**729 900 907**	0.008	38	¾
32		10	**729 900 908**	0.007	44	1
40		10	**729 900 909**	0.016	52	1 ¼
50		10	**729 900 910**	0.032	62	1 ½
63		10	**729 900 911**	0.059	76	2
75	2 ½	10	**729 900 912**	0.095	88	2 ½
90		10	**729 900 913**	0.161	102	3
110		10	**729 900 914**	0.282	122	4
	⅜	10	**729 901 905**	0.002	28	
	½	10	**729 901 906**	0.004	32	
	¾	10	**729 901 907**	0.008	38	
	1	10	**729 901 908**	0.015	44	
	1 ¼	10	**729 901 909**	0.027	52	
	1 ½	10	**729 901 910**	0.050	62	
	2	10	**729 901 911**	0.098	76	
	3	10	**729 901 913**	0.266	102	
	4	10	**729 901 914**	0.476	122	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com