
Data sheet

valid from: 4/1/26





Adaptor PVC-U metric Rp

Model:

- With solvent cement spigot metric and parallel female thread Rp
- Connection to plastic thread only
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

d (mm)	Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	D (mm)	L (mm)
20	Rp	½	10	**721 900 406**	10	0.012	22	28	37
25	Rp	¾	10	**721 900 407**	10	0.018	25	34	41
32	Rp	1	10	**721 900 408**	10	0.035	29	42	48
40	Rp	1 ¼	10	**721 900 409**	10	0.063	34	52	56
50	Rp	1 ½	10	**721 900 410**	10	0.097	40	62	61
63	Rp	2	10	**721 900 411**	5	0.170	49	77	74

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com