
Data sheet

valid from: 4/1/26





Adaptor socket nipple PVC-U metric R

Model:

- With solvent cement spigot/socket reducing metric and taper male thread R
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

d (mm)	Thread Type	Size (inch)	PN (bar)	d1 (mm)	Code	SP	Weight (kg)	z (mm)	z1 (mm)	s (mm)
12	R	⅜	16	16	**721 910 555**	10	0.010	35	23	27
16	R	½	16	20	**721 910 556**	10	0.016	42	28	32
20	R	¾	16	25	**721 910 557**	10	0.023	47	31	36
25	R	1	16	32	**721 910 558**	10	0.040	54	35	46
32	R	1 ¼	16	40	**721 910 559**	10	0.061	60	38	55
40	R	1 ½	16	50	**721 910 560**	10	0.094	66	40	65
50	R	2	16	63	**721 910 561**	5	0.164	78	47	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com