

Data sheet

valid from: 4/1/26





PRO-FIT reducing bush PVC-U metric

Model:

- Outlet: A and B = Solvent cemented spigot in combination with reducing socket metric

d (mm)	d1 (mm)	d2 (mm)	d3 (mm)	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	z1 (mm)	z2 (mm)	L (mm)
10	14	8	12		16	**721 910 903**	10	0.003	15	15	3	27
12	16	8	12		16	**721 910 905**	10	0.004	18	18	6	30
12	16	10	16		16	**721 910 906**	10	0.004	18	18	6	30
16	20	10	16		16	**721 910 908**	10	0.003	21	19	7	33
16	20	12	16		16	**721 910 909**	10	0.004	21	19	7	33
20	25	12	16		16	**721 910 910**	10	0.008	25	21	9	37
20	25	16	20		16	**721 910 911**	10	0.008	25	23	9	39
25	32	12	16		16	**721 910 912**	10	0.014	30	23	11	42
25	32	16	20		16	**721 910 913**	10	0.015	30	26	12	44
25	32	20	25		16	**721 910 914**	10	0.017	30	27	11	46
32	40	16	20		16	**721 910 915**	10	0.025	36	28	14	50
32	40	20	25		16	**721 910 916**	10	0.026	36	30	14	52
32	40	25	32		16	**721 910 917**	10	0.031	36	33	14	55
40	50	20	25		16	**721 910 918**	10	0.045	44	34	18	60
40	50	25	32		16	**721 910 919**	10	0.052	44	37	18	63
40	50	32	40		16	**721 910 920**	10	0.058	44	40	18	66
50	63	25	32		16	**721 910 921**	5	0.092	54	42	23	73
50	63	32	40		16	**721 910 922**	5	0.098	54	45	23	76
50	63	40	50		16	**721 910 923**	5	0.111	54	49	23	80
63	75	32	40		16	**721 910 924**	5	0.127	62	46	24	84
63	75	40	50		16	**721 910 925**	5	0.139	62	50	24	88
63	75	50	63		16	**721 910 926**	5	0.167	62	55	24	93
75	90	40	50	2 ½	16	**721 910 927**	10	0.224	74	56	30	100
75	90	50	63	2 ½	16	**721 910 928**	10	0.253	74	61	30	105
75	90	63	75	2 ½	16	**721 910 929**	10	0.265	74	68	30	112

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com