

Data sheet

valid from: 4/1/26







Reducing bush PVC-U metric Rp

Model:

- With solvent cement spigot metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

	d (mm)	Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	D (mm)	L (mm)	s (mm)
*	12	Rp	¼	16	**721 910 404**	10	0.008	3	20	27	22
	20	Rp	⅜	16	**721 910 434**	10	0.014	7	25	35	
	25	Rp	½	16	**721 910 437**	10	0.021	7	30	41	
	32	Rp	¾	16	**721 910 441**	10	0.032	15	35	48	
	40	Rp	1	16	**721 910 446**	10	0.058	20	45	56	
	50	Rp	1 ¼	16	**721 910 452**	10	0.097	20	55	66	
	63	Rp	1 ½	16	**721 910 458**	5	0.151	10	62	77	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com