
Data sheet

valid from: 4/1/26





Adaptor socket PVC-U metric Rp

Model:

- With solvent cement socket metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

d (mm)	Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	L (mm)	s (mm)
12	Rp	¼	16	**721 910 204**	10	0.010	4	27	22
16	Rp	⅜	16	**721 910 205**	10	0.016	5	31	27
20	Rp	½	16	**721 910 206**	10	0.025	5	36	32
25	Rp	¾	16	**721 910 207**	10	0.032	5	40	36
32	Rp	1	16	**721 910 208**	10	0.057	5	45	46
40	Rp	1 ¼	16	**721 910 209**	10	0.087	5	51	55
50	Rp	1 ½	16	**721 910 210**	10	0.126	7	59	65
63	Rp	2	16	**721 910 211**	5	0.206	7	69	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com