
Data sheet

valid from: 4/1/26





Adaptor bush equal PVC-U metric R

Model:

- With solvent cement socket metric and taper male thread R
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

	d (mm)	d (inch)	Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	L (mm)	s (mm)
*	16	⅜	R	⅜	16	**721 910 705**	10	0.011	20	34	27
*	20	½	R	½	16	**721 910 706**	10	0.018	24	40	32
*	25	¾	R	¾	16	**721 910 707**	10	0.025	25	44	36
*	32	1	R	1	16	**721 910 708**	10	0.039	28	50	46
*	40	1 ¼	R	1 ¼	16	**721 910 709**	10	0.061	31	57	55
*	50	1 ½	R	1 ½	16	**721 910 710**	10	0.092	32	63	65
*	63	2	R	2	16	**721 910 711**	5	0.161	38	76	80
*	75	2 ½	R	2 ½	10	**721 910 712**	6	0.227	42	86	90
	90	3	R	3	10	**721 910 713**	5	0.389	46	97	110
	110	4	R	4	10	**721 910 714**	5	0.572	53	114	130
		⅜	R	⅜	15	**721 911 705**	10	0.013	20	34	27
		½	R	½	15	**721 911 706**	10	0.017	24	40	32
		¾	R	¾	15	**721 911 707**	10	0.022	25	44	36
		1	R	1	15	**721 911 708**	10	0.037	28	50	46
		1 ¼	R	1 ¼	15	**721 911 709**	10	0.055	31	57	55
		1 ½	R		15	**721 911 710**	10	0.097	32	63	65
		2	R	2	15	**721 911 711**	5	0.176	38	76	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com