

Data sheet

valid from: 4/6/26





Adaptor socket PVC-U BS Inch Rp

Model:

- With solvent cement socket BS Inch and parallel female thread Rp
- Do not use thread sealing pastes that are harmful to PVC-U
- Install with low mechanical stress and avoid large cyclic temperature changes
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads

Thread Type	Size (inch)	PN (bar)	d (inch)	Code	SP	Weight (kg)	z (mm)	L (mm)	s (mm)
Rp		15	⅜	**721 911 005**	10	0.016	4	31	27
Rp		15	½	**721 911 006**	10	0.024	4	35	32
Rp	¾	15	¾	**721 911 007**	10	0.030	3	40	36
Rp	1	15	1	**721 911 008**	10	0.055	3	45	46
Rp	1 ¼	15	1 ¼	**721 911 009**	10	0.083	3	51	55
Rp	1 ½	15	1 ½	**721 911 010**	10	0.127	8	59	65
Rp	2	15	2	**721 911 011**	5	0.215	8	69	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com