
Data sheet

valid from: 4/1/26





Adaptor nipple PVC-U Inch BS R

Model:

- With solvent cement spigot BS Inch and taper male thread R
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	L (mm)
R	⅜	15	**721 913 905**		0.007	43
R	½	15	**721 913 906**		0.013	50
R	¾	15	**721 913 907**		0.022	56
R	1	15	**721 913 908**		0.034	63
R	1 ¼	15	**721 913 909**		0.060	75
R	1 ½	15	**721 913 910**		0.082	88
R	2	15	**721 913 911**		0.111	88
R	3	15	**721 913 913**		0.253	128
R		15	**721 913 915**		0.486	153

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com