
Data sheet

valid from: 4/1/26





Elbow 90° PVC-C metric Rp

Model:

- With solvent cement socket metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-C

Rp (inch)	d (mm)	PN (bar)	Code	SP	Weight (kg)	z1 (mm)	z2 (mm)	D (mm)	L (mm)
½	20	16	**723 100 206**	10	0.024	11	14	30	27
¾	25	16	**723 100 207**	10	0.037	14	17	35	33
1	32	16	**723 100 208**	10	0.063	17	22	45	39
1 ¼	40	16	**723 100 209**	10	0.134	23	27	55	50
1 ½	50	16	**723 100 210**	5	0.199	27	36	62	58
2	63	16	**723 100 211**	10	0.337	33	46	75	73

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com