

# Data sheet

valid from: 8/27/26






1




## PROGEF Standard Tee 90° reduced
## SDR17.6/PN6

**Model:**

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- IR = Infrared welding compatible

[1]with IR welded reducer
* SDR11 Branch

| | d (mm) | d1 (mm) | PN (bar) | FM | Code | Weight (kg) | L (mm) | L1 (mm) | L2 (mm) | L3 (mm) | e (mm) | e1 (mm) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| * | 63 | 32 | 6 | IR | **727 208 301** | 0.120 | 65 | 70 | 25 | 25 | 3.6 | 2.9 |
| | 63 | 50 | 6 | IR | **727 208 302** | 0.124 | 65 | 70 | 25 | 25 | 3.6 | 2.9 |
| * | 75 | 32 | 6 | IR | **727 208 303** | 0.178 | 70 | 75 | 25 | 25 | 4.3 | 2.9 |
| | 75 | 50 | 6 | IR | **727 208 304** | 0.182 | 70 | 75 | 25 | 25 | 4.3 | 2.9 |
| | 75 | 63 | 6 | IR | **727 208 305** | 0.190 | 70 | 75 | 25 | 25 | 4.3 | 3.6 |
| | 90 | 50 | 6 | IR | **727 208 307** | 0.305 | 80 | 85 | 25 | 25 | 5.1 | 2.9 |
| | 90 | 63 | 6 | IR | **727 208 308** | 0.315 | 80 | 85 | 25 | 25 | 5.1 | 3.6 |
| | 90 | 75 | 6 | IR | **727 208 309** | 0.320 | 80 | 85 | 25 | 25 | 5.1 | 4.3 |
| * | 110 | 32 | 6 | IR | **727 208 310** | 0.489 | 90 | 95 | 30 | 25 | 6.3 | 2.9 |
| | 110 | 50 | 6 | IR | **727 208 311** | 0.490 | 90 | 95 | 30 | 25 | 6.3 | 2.9 |
| | 110 | 63 | 6 | IR | **727 208 312** | 0.491 | 90 | 95 | 30 | 25 | 6.3 | 3.6 |
| | 110 | 75 | 6 | IR | **727 208 313** | 0.500 | 90 | 95 | 30 | 25 | 6.3 | 4.3 |
| | 110 | 90 | 6 | IR | **727 208 314** | 0.514 | 90 | 95 | 30 | 25 | 6.3 | 5.1 |
| 1 | 125 | 63 | 6 | IR | **727 208 015** | 1.300 | 125 | 212 | 50 | 20 | 7.1 | 3.6 |
| 1 | 125 | 90 | 6 | IR | **727 208 016** | 1.400 | 125 | 229 | 50 | 41 | 7.1 | 5.1 |
| 1 | 125 | 110 | 6 | IR | **727 208 017** | 1.400 | 125 | 218 | 50 | 42 | 7.1 | 6.3 |
| 1 | 140 | 75 | 6 | IR | **727 208 018** | 2.000 | 160 | 255 | 63 | 41 | 8.0 | 4.3 |
| 1 | 140 | 90 | 6 | IR | **727 208 019** | 2.100 | 160 | 251 | 63 | 42 | 8.0 | 5.1 |
| 1 | 140 | 110 | 6 | IR | **727 208 020** | 2.100 | 160 | 240 | 63 | 43 | 8.0 | 6.3 |
| | 160 | 63 | 6 | IR | **727 208 321** | 1.535 | 142 | 135 | 50 | 30 | 9.1 | 3.6 |
| | 160 | 75 | 6 | IR | **727 208 322** | 1.550 | 142 | 135 | 50 | 30 | 9.1 | 4.3 |
| | 160 | 90 | 6 | IR | **727 208 323** | 1.567 | 142 | 135 | 50 | 30 | 9.1 | 5.1 |
| | 160 | 110 | 6 | IR | **727 208 324** | 1.577 | 142 | 135 | 50 | 30 | 9.1 | 6.3 |
| 1 | 160 | 125 | 6 | IR | **727 208 025** | 2.800 | 163 | 275 | 60 | 32 | 9.1 | 7.1 |
| | 180 | 63 | 6 | IR | **727 208 072** | 5.860 | 217 | 301 | 97 | 28 | 10.2 | 3.8 |
| | 180 | 63 | 6 | IR | **727 208 394** | 5.860 | 217 | 301 | 97 | 28 | 10.2 | 3.8 |
| | 180 | 90 | 6 | IR | **727 208 073** | 4.600 | 217 | 352 | 97 | 42 | 10.2 | 5.1 |
| | 180 | 90 | 6 | IR | **727 208 395** | 4.600 | 217 | 352 | 97 | 42 | 10.2 | 5.1 |
| | 180 | 110 | 6 | IR | **727 208 074** | 4.620 | 217 | 357 | 97 | 42 | 10.2 | 6.3 |
| | 180 | 110 | 6 | IR | **727 208 396** | 4.620 | 217 | 357 | 97 | 42 | 10.2 | 6.3 |
| | 180 | 160 | 6 | IR | **727 208 076** | 4.700 | 217 | 342 | 97 | 52 | 10.2 | 9.1 |
| | 180 | 160 | 6 | IR | **727 208 397** | 4.700 | 217 | 342 | 97 | 52 | 10.2 | 9.1 |
| 1 | 200 | 160 | 6 | IR | **727 208 035** | 5.900 | 220 | 325 | 94 | 40 | 11.4 | 9.1 |
| 1 | 200 | 180 | 6 | IR | **727 208 036** | 6.000 | 220 | 325 | 94 | 54 | 11.4 | 10.2 |
| | 225 | 90 | 6 | IR | **727 208 338** | 3.350 | 155 | 165 | 40 | 30 | 12.8 | 5.1 |
| | 225 | 110 | 6 | IR | **727 208 339** | 3.330 | 155 | 165 | 40 | 30 | 12.8 | 6.3 |
| | 225 | 160 | 6 | IR | **727 208 341** | 3.427 | 155 | 165 | 40 | 30 | 12.8 | 9.1 |
| 1 | 250 | 160 | 6 | IR | **727 208 043** | 8.900 | 225 | 389 | 67 | 52 | 14.2 | 9.1 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com