
Data sheet

valid from: 4/1/26





PROGEF Standard Reducer
SDR17.6/PN6

Model:

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- IR = Infrared welding compatible

	d (mm)	d1 (mm)	PN (bar)	FM	Code	Weight (kg)	L (mm)	L1 (mm)	L2 (mm)	e (mm)	e1 (mm)
	50	40	6	IR	**727 908 713**	0.018	134	56	52	2.9	2.3
	63	40	6	IR	**727 908 901**	0.020	65	16	12	3.6	2.3
	63	50	6	IR	**727 908 718**	0.055	87	29	27	3.6	2.9
	75	40	6	IR	**727 908 904**	0.041	65	20	20	4.3	2.3
	75	50	6	IR	**727 908 465**	0.047	65	20	20	4.5	3.0
	75	63	6	IR	**727 908 464**	0.053	65	20	20	4.5	3.8
	90	63	6	IR	**727 908 471**	0.079	75	22	19	5.4	3.8
	90	75	6	IR	**727 908 470**	0.090	75	21	19	5.4	4.5
	110	63	6	IR	**727 908 472**	0.149	90	28	28	6.6	3.8
	110	75	6	IR	**727 908 477**	0.149	90	28	18	6.6	4.5
	110	90	6	IR	**727 908 476**	0.158	90	28	20	6.6	5.4
	125	110	6	IR	**727 908 738**	0.250	103	42	42	7.1	6.3
	140	110	6	IR	**727 908 742**	0.320	120	53	43	8.0	6.3
	140	125	6	IR	**727 908 916**	0.353	115	35	32	8.0	7.1
	160	110	6	IR	**727 908 746**	0.500	129	40	34	9.1	6.3
	160	140	6	IR	**727 908 748**	0.560	125	49	38	9.1	8.0
	180	90	6	IR	**727 908 749**	0.600	145	53	42	10.2	5.1
	180	110	6	IR	**727 908 750**	0.620	150	55	42	10.2	6.3
	180	125	6	IR	**727 908 751**	0.620	143	52	40	10.2	7.1
	180	140	6	IR	**727 908 752**	0.640	135	51	47	10.2	8.0
	180	160	6	IR	**727 908 753**	0.700	135	55	52	10.2	9.1
	200	160	6	IR	**727 908 930**	0.805	151	50	40	11.4	9.1
	200	180	6	IR	**727 908 758**	0.920	145	62	54	11.4	10.2
	225	110	6	IR	**727 908 936**	1.001	160	55	35	12.8	6.3
	225	160	6	IR	**727 908 934**	1.082	160	55	40	12.8	9.1
	225	180	6	IR	**727 908 762**	1.160	166	64	57	12.8	10.2
	225	200	6	IR	**727 908 932**	1.184	160	55	50	12.8	11.4
	250	160	6	IR	**727 908 765**	1.530	174	64	52	14.2	9.1
	250	225	6	IR	**727 908 768**	1.890	180	65	65	14.2	12.8
1	280	225	6	IR	**727 908 772**	2.370	200	70	55	15.9	12.8
1	280	250	6	IR	**727 908 773**	2.540	200	73	62	15.9	14.2
1	315	225	6	IR	**727 908 776**	3.320	237	84	59	17.9	12.8
1	315	250	6	IR	**727 908 777**	3.375	233	84	64	17.9	14.2
1	315	280	6	IR	**727 908 778**	3.510	227	85	72	17.9	15.9
1	355	315	6	IR	**727 908 957**	2.400	245	90	80	20.1	17.9
1	400	315	6		**727 908 972**	3.600	260	95	80	22.7	17.9
1	400	355	6		**727 908 971**	3.100	260	95	90	22.7	20.1
	450	280	6		**727 908 967**	6.000	230	60	70	25.5	15.9
	450	315	6		**727 908 984**	5.400	230	60	80	25.5	17.9
	450	355	6		**727 908 988**	5.000	230	60	90	25.5	20.1
	450	400	6		**727 908 989**	5.000	230	60	95	25.5	22.7
	500	315	6		**727 908 993**	8.100	230	60	80	28.4	17.9
	500	355	6		**727 908 994**	7.300	230	60	95	28.4	20.1
	500	400	6		**727 908 998**	6.700	230	60	95	28.4	22.7
	500	450	6		**727 908 999**	5.500	230	60	60	28.4	25.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com