
Data sheet

valid from: 8/27/26





PROGEF Standard adaptor socket metric Rp

Model:

- Material: PP-H
- With butt fusion spigot **SDR11** and BSP parallel female thread Rp, reinforced
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Do not use thread sealing pastes that are harmful to PP
- Install with low mechanical stress and avoid large cyclic temperature changes

d (mm)	Thread Type	Size (inch)	PN (bar)	FM	Code	SP	Weight (kg)	L (mm)	L1 (mm)	s (mm)	e (mm)
20	Rp	½	10	IR	**727 910 266**	10	0.017	49	23	32	1.9
25	Rp	¾	10	IR	**727 910 267**	10	0.022	50	23	36	2.3
32	Rp	1	10	IR	**727 910 268**	10	0.038	54	23	46	2.9
40	Rp	1 ¼	10	IR	**727 910 269**	10	0.066	56	23	55	3.7
50	Rp	1 ½	10	IR	**727 910 270**	10	0.090	60	23	65	4.6
63	Rp	2	10	IR	**727 910 271**	20	0.123	62	23	80	5.8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com