
Data sheet

valid from: 4/2/26





Elbow 90° ABS metric Rp

Model:

- With solvent cement socket metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to ABS

d (mm)	Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z1 (mm)	z2 (mm)	D (mm)	L (mm)
20	Rp	½	10	**729 100 206**	10	0.018	13	11	30	27
25	Rp	¾	10	**729 100 207**	10	0.028	16	15	35	33
32	Rp	1	10	**729 100 208**	10	0.047	19	19	45	39
40	Rp	1 ¼	10	**729 100 209**	10	0.088	23	27	55	50
50	Rp	1 ½	10	**729 100 210**	5	0.128	27	36	62	58
63	Rp	2	10	**729 100 211**	5	0.233	33	46	75	73

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com