
Data sheet

valid from: 4/2/26





Elbow 45° ABS metric

- >d225 - maximum operating temperature: +40°C

	d (mm)	d (inch)	Size (inch)	PN (bar)	Code	SP	Weight (kg)	D (mm)	L (mm)	z (mm)	closest inch (inch)
	20			16	**729 150 106**	10	0.009	25	21	5	½
	25			16	**729 150 107**	10	0.013	31	25	6	¾
	32			10	**729 150 108**	10	0.026	40	30	8	1
	40			10	**729 150 109**	10	0.044	49	36	10	1 ¼
	50			10	**729 150 110**	5	0.079	61	43	12	1 ½
	63			10	**729 150 111**	10	0.143	76	52	14	2
*	75	2 ½	2 ½	10	**729 150 112**	5	0.225	89	61	17	2 ½
	90			10	**729 150 113**	4	0.363	107	71	20	3
	110			10	**729 150 114**	10	0.567	131	89	28	4
*	140	5	5	10	**729 150 116**	1	1.175	162	108	32	5
	160			10	**729 150 117**	4	1.713	185	122	36	6
	200			10	**729 150 119**	1	2.546	225	149	43	8
	225			10	**729 150 120**	1	3.162	250	168	49	8
			½	15	**729 151 106**	10	0.010	28	24	7	
			¾	15	**729 151 107**	10	0.015	33	29	8	
			1	15	**729 151 108**	10	0.027	41	33	10	
			1 ¼	15	**729 151 109**	10	0.046	51	40	11	
			1 ½	15	**729 151 110**	5	0.068	57	41	11	
			2	15	**729 151 111**	10	0.134	72	51	15	
			3	15	**729 151 113**	5	0.407	109	72	21	
			4	15	**729 151 115**	5	0.714	135	89	26	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com