
Data sheet

valid from: 4/2/26





Tee 90° ABS metric

- >d225 - maximum operating temperature: +40°C

	d (mm)	Size (inch)	PN (bar)	Code	SP	Weight (kg)	D (mm)	L (mm)	z (mm)	closest inch (inch)
	20		16	**729 200 106**	10	0.015	25	27	11	½
	25		16	**729 200 107**	10	0.025	31	33	14	¾
	32		10	**729 200 108**	10	0.042	40	39	17	1
	40		10	**729 200 109**	10	0.078	49	47	21	1 ¼
	50		10	**729 200 110**	5	0.134	61	57	26	1 ½
	63		10	**729 200 111**	5	0.255	76	72	34	2
*	75	2 ½	10	**729 200 112**	6	0.404	90	84	40	2 ½
	90		10	**729 200 113**	4	0.664	107	98	47	3
	110		10	**729 200 114**	6	1.010	133	116	55	4
*	140	5	10	**729 200 116**	2	2.570	169	147	71	5
	160		10	**729 200 117**	4	3.752	193	167	81	6
	200		10	**729 200 119**	1	4.446	225	207	101	8
	225		10	**729 200 120**	1	6.860	256	233	114	8
		½	15	**729 201 106**	10	0.028	30	30	13	
		¾	15	**729 201 107**	10	0.039	35	37	16	
		1	15	**729 201 108**	10	0.061	43	43	19	
		1 ¼	15	**729 201 109**	10	0.075	53	51	22	
		1 ½	15	**729 201 110**	5	0.152	58	56	26	
		2	15	**729 201 111**	5	0.307	73	68	32	
		3	15	**729 201 113**	5	0.703	107	97	46	
		4	15	**729 201 115**	2	1.417	138	122	59	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com