
Data sheet

valid from: 4/2/26





Reducing bush ABS metric Rp

Model:

- With solvent cement spigot metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to ABS

d (mm)	Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	D (mm)	L (mm)
20	Rp	⅜	10	**729 910 434**	10	0.012	7	25	35
25	Rp	½	10	**729 910 437**	10	0.017	7	30	41
32	Rp	¾	10	**729 910 441**	10	0.025	15	35	48
40	Rp	1	10	**729 910 446**	10	0.046	20	45	56
50	Rp	1 ¼	10	**729 910 452**	10	0.077	20	55	66
63	Rp	1 ½	10	**729 910 458**	5	0.120	10	62	77

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com