

Data sheet

valid from: 4/2/26





Socket ABS metric Rp

Model:

- With solvent cement socket metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to ABS

d (mm)	Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	closest inch (inch)	z (mm)	L (mm)	s (mm)
20	Rp	½	10	**729 910 206**	10	0.020	½	4	35	32
25	Rp	¾	10	**729 910 207**	10	0.025	¾	3	40	36
32	Rp	1	10	**729 910 208**	10	0.045	1	3	45	46
40	Rp	1 ¼	10	**729 910 209**	10	0.067	1 ¼	5	51	55
50	Rp	1 ½	10	**729 910 210**	10	0.099	1 ½	7	59	65
63	Rp	2	10	**729 910 211**	5	0.167	2	7	69	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com