
Data sheet

valid from: 4/2/26





Socket ABS metric

Model:

- With cemented sockets
- * = adaptor socket metric / british standard

*	Standard	d (mm)	d (inch)	PN (bar)	Code	SP	Weight (kg)	D (mm)	L (mm)	z (mm)
	Metric	20		16	**729 910 106**	10	0.007	26	35	3
	Metric	25		16	**729 910 107**	10	0.012	32	41	3
	Metric	32		10	**729 910 108**	10	0.020	40	47	3
	Metric	40		10	**729 910 109**	10	0.035	49	55	3
	Metric	50		10	**729 910 110**	10	0.060	61	65	3
	Metric	63		10	**729 910 111**	10	0.110	76	79	3
*	Metric / BS	75	2 ½	10	**729 910 112**	20	0.145	87	92	4
	Metric	90		10	**729 910 113**	10	0.241	104	107	5
	Metric	110		10	**729 910 114**	5	0.566	131	132	5
*	Metric / BS	140	5	10	**729 910 116**	2	0.813	162	159	7
	Metric	160		10	**729 910 117**	2	1.176	183	180	8
	Metric	200		10	**729 910 119**	1	1.511	221	221	9
	Metric	225		10	**729 910 120**	1	2.537	253	248	10
	BS		½	15	**729 911 106**	10	0.008	27	38	3
	BS		¾	15	**729 911 107**	10	0.011	33	45	3
	BS		1	15	**729 911 108**	10	0.017	41	51	3
	BS		1 ¼	15	**729 911 109**	10	0.036	51	60	3
	BS		1 ½	15	**729 911 110**	10	0.051	58	64	3
	BS		2	15	**729 911 111**	5	0.095	72	78	5
	BS		3	15	**729 911 113**	10	0.262	104	108	7
	BS		4	15	**729 911 115**	5	0.470	134	135	8
*	Metric / BS	20	½	10	**729 913 106**	1	0.010	27	38	5
*	Metric / BS	25	¾	10	**729 913 107**	1	0.016	33	45	5
*	Metric / BS	32	1	10	**729 913 108**	1	0.025	41	51	5
*	Metric / BS	40	1 ¼	10	**729 913 109**	1	0.045	51	60	5
*	Metric / BS	50	1 ½	10	**729 913 110**	1	0.070	59	65	4
*	Metric / BS	63	2	10	**729 913 111**	1	0.130	75	79	5
*	Metric / BS	90	3	10	**729 913 113**	2	0.365	104	108	6
*	Metric / BS	110	4	10	**729 913 115**	1	0.630	134	135	7

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com