
Data sheet

valid from: 4/2/26





SYGEF Standard fixed flange
For socket fusion metric
Combined jointing face: flat and serrated

Model:

- Material: PVDF
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10

AL: number of holes

d (mm)	DN (mm)	PN (bar)	Size (inch)	Code	Weight (kg)	D1 (mm)	D2 (mm)	D3 (mm)	D4 (mm)	H (mm)	H1 (mm)	AL	z (mm)
20	15	16	½	**735 740 106**	0.121	27	65	93	14	12	19	4	5
25	20	16	¾	**735 740 107**	0.162	33	75	103	14	13	21	4	4
32	25	16	1	**735 740 108**	0.229	40	85	115	14	14	23	4	4
40	32	16	1 ¼	**735 740 109**	0.340	50	100	137	18	15	25	4	4
50	40	16	1 ½	**735 740 110**	0.409	61	110	147	18	16	27	4	4
63	50	16	2	**735 740 111**	0.551	76	125	162	18	18	31	4	4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com