


Data sheet

valid from: 4/2/26









SYGEF Standard flange adaptor
Jointing face serrated PN16

Model:

- Material: PVDF

d (mm)	DN (mm)	PN (bar)	SDR	FM	Type	Code	Weight (kg)
20	15	16	21	BCF, IR	A	**735 798 806**	0.029
25	20	16	21	BCF, IR	B	**735 798 807**	0.046
32	25	16	21	BCF, IR	B	**735 798 808**	0.070
40	32	16	21	BCF, IR	B	**735 798 809**	0.096
50	40	16	21	BCF, IR	B	**735 798 810**	0.136
63	50	16	21	BCF, IR	A	**735 798 811**	0.198
75	65	16	21	BCF, IR	A	**735 798 812**	0.311
90	80	16	21	BCF, IR	B	**735 798 813**	0.394
110	100	16	21	BCF, IR	C	**735 798 814**	0.561
140	125	16	21	IR	C	**735 798 816**	0.861
160	150	16	21	IR	C	**735 798 817**	1.200
200	200	16	21	IR	C	**735 798 819**	1.900
225	200	16	21	IR	C	**735 798 820**	2.000

d (mm)	L (mm)	L1 (mm)	L2 (mm)	D (mm)	D1 (mm)	D2 (mm)	D3 (mm)	e (mm)
20	54	6		26	45	15		1.9
25	56	7	4	32	58	20	54	1.9
32	58	7	4	40	68	26	63	2.4
40	68	8	4	49	78	34	73	2.4
50	69	8	4	60	88	43	82	3.0
63	72	9		75	102	56		3.0
75	80	10		89	122	66		3.6
90	81	12	4	105	138	78	133	4.3
110	81	13		125	158	100		5.3
140	90	16		155	188	127		6.7
160	93	17		175	212	151		7.7
200	102	22		232	268	207		9.6
225	102	22		235	268	207		10.8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com