
Data sheet

valid from: 4/2/26





SYGEF Standard adaptor nipple male thread R PN16

Model:

- Avoid stresses when installing and large changes in temperature
- Material: PVDF
- With butt fusion spigot and BSP tapered male thread
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF

d (mm)	DN (mm)	Size (inch)	PN (bar)	SDR	FM	Thread Type	Code	Weight (kg)	L (mm)	L1 (mm)	s (mm)	e (mm)
20	15	⅜	16	21	BCF, IR	R	**735 910 555**	0.024	50	26	32	1.9
20	15	½	16	21	BCF, IR	R	**735 910 556**	0.025	53	26	32	1.9
25	20	¾	16	21	BCF, IR	R	**735 910 557**	0.035	55	26	36	1.9
32	25	1	16	21	BCF, IR	R	**735 910 558**	0.054	57	26	46	2.4
40	32	1 ¼	16	21	BCF, IR	R	**735 910 559**	0.076	60	26	55	2.4
50	40	1 ½	16	21	BCF, IR	R	**735 910 560**	0.123	63	26	65	3.0
63	50	2	16	21	BCF, IR	R	**735 910 561**	0.166	69	27	75	3.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com