
Data sheet

valid from: 4/2/26





SYGEF Standard adaptor nipple male thread metric R PN16

Model:

- Material: PVDF
- With socket fusion spigot metric and BSP tapered male thread
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF
- Avoid stresses when installing and large changes in temperature

d (mm)	DN (mm)	Thread Type	Size (inch)	PN (bar)	Code	Weight (kg)	L (mm)	z (mm)	s (mm)
16	10	R	⅜	16	**735 910 505**	0.014	35	12	27
20	15	R	½	16	**735 910 506**	0.025	53	25	32
25	20	R	¾	16	**735 910 507**	0.033	55	24	36
32	25	R	1	16	**735 910 508**	0.053	57	22	46
40	32	R	1 ¼	16	**735 910 509**	0.076	60	21	55
50	40	R	1 ½	16	**735 910 510**	0.113	63	19	65
63	50	R	2	16	**735 910 511**	0.161	69	18	75

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com