


Data sheet

valid from: 4/17/26





Type A



Type B

SYGEF Standard cap PN16

Model:

- Material: PVDF
- Type A: injection molded
- Type B: machined, incl. facing mark (must not be exceeded)

d (mm)	DN (mm)	PN (bar)	SDR	FM	Type	Code	L (mm)	e (mm)
20	15	16	21	BCF, IR	A	**735 968 006**	47.0	1.9
25	20	16	21	BCF, IR	A	**735 968 007**	47.0	1.9
32	25	16	21	BCF, IR	A	**735 968 008**	52.0	2.4
40	32	16	21	IR	B	**735 968 309**	30.0	2.4
50	40	16	21	IR	B	**735 968 310**	30.0	3.0
63	50	16	21	IR	B	**735 968 311**	30.0	3.0
75	65	16	21	BCF, IR	A	**735 968 012**	64.0	3.6
90	80	16	21	BCF, IR	A	**735 968 013**	70.5	4.3
110	100	16	21	BCF, IR	A	**735 968 014**	77.5	5.3
140	125	16	21	IR	B	**735 968 316**	45.0	6.7
160	150	16	21	IR	B	**735 968 317**	46.0	7.7
200	200	16	21	IR	B	**735 968 319**	54.0	9.6
225	200	16	21	IR	B	**735 968 320**	57.0	10.8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com