


Data sheet

valid from: 8/27/26









PROGEF Standard PP-H Ball valve type 546 Pro with PPA
DA (Double Acting)
With fusion sockets PP-H ISO
With manual override

Model:

- Control pressure supply through integrated NAMUR interface according VDI/VDE 3845
- Full plastic solution (actuator housing made of PP-GF)
- Visual position indicator
- Integrated stainless steel mounting inserts
- z-dimension, valve end and union nut are compatible with type 546 (1st Generation)

Option:

- Position feedback through double sensor with LED (PNP, NPN and NAMUR)
- Positioner RPC, RPC D, RPC PID
- Individual configuration of the valve possible

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value (Δp=1 bar) (l/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
16	10	⅜	10	70	**199 251 082**	1	1.500	**199 251 092**	1	1.500
20	15	½	10	185	**199 251 083**	1	1.500	**199 251 093**	1	1.500
25	20	¾	10	350	**199 251 084**	1	1.600	**199 251 094**	1	1.600
32	25	1	10	700	**199 251 085**	1	1.152	**199 251 095**	1	1.700
40	32	1 ¼	10	1000	**199 251 086**	1	2.800	**199 251 096**	1	2.800
50	40	1 ½	10	1600	**199 251 087**	1	3.100	**199 251 097**	1	3.100
63	50	2	10	3100	**199 251 088**	1	4.000	**199 251 098**	1	4.000

d (mm)	Actuator	B3 (mm)	B5 (mm)	da2 (mm)	DE1 (mm)	E (mm)	G (mm)	G1 (mm)	H (mm)	H2 (mm)	H4 (mm)	L (mm)	Lz (mm)	M (mm)	R2
16	PPA08	25	16.2	33	50	74	M6	M5	215	20	12	93	28	128	R150
20	PPA08	25	16.2	33	50	74	M6	M5	215	20	12	95	28	128	R150
25	PPA08	25	17.5	33	58	74	M6	M5	219	20	12	109	33	128	R150
32	PPA08	25	17.5	33	68	74	M6	M5	238	20	12	119	36	128	R150
40	PPA15	45	23.3	33	84	94	M8	M5	244	20	15	135	43	159	R150
50	PPA15	45	23.3	33	97	94	M8	M5	273	20	15	147	45	159	R150
63	PPA40	45	24.3	33	124	120	M8	M5	288	20	15	168	51	184	R150

d (mm)	V1 (mm)	X5 (mm)	X6 (mm)	X7 (mm)	X8 (mm)	X9 (mm)	X10 (mm)	z (mm)
16	27	80	30	43	78	132	38.00	67
20	27	80	30	43	78	132	38.00	66
25	30	80	30	43	78	132	41.90	77
32	36	80	30	51	78	132	47.00	83
40	44	80	30	51	78	132	53.50	99
50	51	80	30	62	78	132	62.75	105
63	64	80	30	62	78	132	77.00	117

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com