Data sheet

valid from: 4/7/26




SYGEF Standard Ball valve type 127
24V
With manual emergency override
With fusion sockets PVDF ISO

Model:


- IP68 Rating
- Factory set control range 90°<)
- Heating element, position feedback (Open/Close)
- Integrated stainless steel mounting inserts

Option:


- Other valve and actuator configurations available
- Optional accessories: Fail-safe return unit



d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value (Δp=1 bar) (l/min)	FKM Code	Weight (kg)
16	10	⅜	10	70	**199 127 822**	2.100
20	15	½	10	185	**199 127 823**	2.100
25	20	¾	10	350	**199 127 824**	2.200
32	25	1	10	700	**199 127 825**	2.414
40	32	1 ¼	10	1000	**199 127 826**	2.600
50	40	1 ½	10	1600	**199 127 827**	2.995
63	50	2	10	3100	**199 127 828**	3.800



d (mm)	Actuator	B3 (mm)	DE1 (mm)	E (mm)	G (mm)	H (mm)	H1 (mm)	H4 (mm)	L (mm)	L1 (mm)	Lz (mm)	M (mm)	M1 (mm)	M2 (mm)	z (mm)
16	EA15	25	50	122	M6	197	27	12	93	33	28	161	77	83	67
20	EA15	25	50	122	M6	197	27	12	95	33	28	161	77	83	66
25	EA15	25	58	122	M6	201	30	12	109	33	33	161	77	83	77
32	EA15	25	68	122	M6	207	36	12	119	33	36	161	77	83	83
40	EA15	45	84	122	M8	213	44	15	135	33	43	161	77	83	99
50	EA15	45	97	122	M8	219	51	15	147	33	45	161	77	83	105
63	EA15	45	124	122	M8	234	64	15	168	33	51	161	77	83	117



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com